

 250 kg

 66 kg



Equipo ligero con rotación manual 0° - 90° y basculación neumática 0° - 90° especialmente indicado para procesos de manipulación de vidrio en vertical y horizontal como canteadoras, CNC horizontales, laminadoras, hornos de templar, ensamblaje horizontal de puertas y ventanas, mesas de corte...

Funciona sólo con aire a presión con giro manual 360° muy cómodo y basculación neumática 0° - 90°. El equipo es rápido, preciso y facilita el trabajo sin esfuerzo del operario.

*Light equipment with manual rotation 0° - 90° and pneumatic tilting 0° - 90° indicated for vertical and horizontal glass handling processes, such as edger machines, vertical or horizontal CNC machines, laminate glass machines, tempering furnaces, horizontal assembly of doors and windows, cutting tables ...*

*It works only with pressurized air with a very comfortable 360° manual rotation and pneumatic tilting 0° - 90° are fast and precise to speed up the operator's work and increase efficiency.*




 7 bar - 100 l/min

 40 L/min

 90° - 180° - 270° - 360°

 0° - 90°

 —



 400 kg

 78 kg



Equipo ligero con rotación manual 0° - 90° y basculación neumática 0° - 90° especialmente indicado para procesos de manipulación de vidrio en vertical y horizontal como canteadoras, CNC horizontales, laminadoras, hornos de templar, ensamblaje horizontal de puertas y ventanas, mesas de corte...

Funciona sólo con aire a presión con giro manual 360° muy cómodo y basculación neumática 0° - 90°. El equipo es rápido, preciso y facilita el trabajo sin esfuerzo del operario.

*Light equipment with manual rotation 0° - 90° and pneumatic tilting 0° - 90° indicated for vertical and horizontal glass handling processes, such as edger machines, vertical or horizontal CNC machines, laminate glass machines, tempering furnaces, horizontal assembly of doors and windows, cutting tables ...*

*It works only with pressurized air with a very comfortable 360° manual rotation and pneumatic tilting 0° - 90° are fast and precise to speed up the operator's work and increase efficiency.*




 7 bar - 100 l/min

 40 L/min

 90° - 180° - 270° - 360°

 0° - 90°

 —



 400 kg

 90 kg



Equipo ligero con rotación manual 0° - 90° y basculación neumática 0° - 90° especialmente indicado para procesos de manipulación de vidrio en vertical y horizontal como canteadoras, CNC horizontales, laminadoras, hornos de templar, ensamblaje horizontal de puertas y ventanas, mesas de corte...

Funciona sólo con aire a presión con giro manual 360° muy cómodo y basculación neumática 0° - 90°. El equipo es rápido, preciso y facilita el trabajo sin esfuerzo del operario.

*Light equipment with manual rotation 0° - 90° and pneumatic tilting 0° - 90° indicated for vertical and horizontal glass handling processes, such as edger machines, vertical or horizontal CNC machines, laminate glass machines, tempering furnaces, horizontal assembly of doors and windows, cutting tables ...*

*It works only with pressurized air with a very comfortable 360° manual rotation and pneumatic tilting 0° - 90° are fast and precise to speed up the operator's work and increase efficiency.*

 7 bar - 100 l/min

 40 L/min

 90° - 180° - 270° - 360°

 0° - 90°

 —

