




El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.



Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.


*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

-  OK
-  60 W
-  NO
-  OK
-  220-240VAC (50-60Hz)
-  30 L/min
-  OK - BATTERY 12V





-  300 kg
-  90 kg
-  24 kg
-  0° - 60° - 90°

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.


Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.


*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

-  OK
-  60 W
-  NO
-  OK
-  220-240VAC (50-60Hz)
-  30 L/min
-  OK - BATTERY 12V





 300 kg

 90 kg

 30 kg

 0° - 180°

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.

Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.

*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

 OK



 60 W


 OK

 220-240VAC (50-60Hz)

 30 L/min

 OK - BATTERY 12V





 300 kg

 90 kg

 23 kg

 NO

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.

Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.

*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

 OK


 60 W


 OK

 220-240VAC (50-60Hz)

 30 L/min

 OK - BATTERY 12V





El equipo XL0 es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.


Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.


Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.

The XL0 equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*





-  600 kg
-  300 kg
-  49 kg
-  0° - 60° - 90°

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.


Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.


*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

-  OK
-  60 W
-  NO
-  OK
-  220-240VAC (50-60Hz)
-  30 L/min
-  OK - BATTERY 12V





-  600 kg
-  300 kg
-  55 kg
-  0° - 180°

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.



Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.


*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

-  OK
-  60 W
-  OK
-  220-240VAC (50-60Hz)
-  30 L/min
-  OK - BATTERY 12V





 600 kg

 300 kg

 48 kg

 NO

El equipo XLO es ligero y compacto, con gran capacidad de carga y funcionamiento a batería. Dispone de doble circuito de vacío de seguridad para la manipulación e instalación de vidrio en obra, según la norma EN-13155.

Incorpora nuevos módulos digitales de control en línea con la industria 4.0. Cuenta con indicadores de batería y de nivel de vacío con alarma luminosa y acústica.

Las reducidas dimensiones permiten instalaciones complejas en sitios muy estrechos como entre fachada y andamio.

*The XLO equipment is light and compact, with great charging capacity and battery operation. It has a double safety vacuum circuit for the handling and installation of glass on site, according to the EN-13155 standard.*

*It incorporates new digital control modules in line with industry 4.0. It has battery and vacuum level indicators with light and acoustic alarm.*

*The small dimensions allow complex installations in very narrow places such as between the facade and the scaffolding.*

 OK

 60 W

 OK

 220-240VAC (50-60Hz)

 30 L/min

 OK - BATTERY 12V

